

CERTIFICATE

of conformity with the following European Directives

Low Voltage Directive 2014/35/EU

This certifies that below described products of the applicant:

Renac Power Technology Co., Ltd.

Block C-12, No. 20 Datong Road, Comprehensive Bonded Zone,
Suzhou Hi-Tech District, Suzhou, China

comply to the essential requirements of the above mentioned European Directive and the following standards, taking into account the German national deviations:

Product(s):	Grid-Connected PV Inverter
Model type(s):	R3-30K-G5-L0, R3-30K-G5, R3-30K-G5-L1, R3-30K-G5-L2, R3-30K-G5-L3, R3-30K-G5-L4, R3-33K-G5-L0, R3-33K-G5, R3-33K-G5-L1, R3-33K-G5-L2, R3-33K-G5-L3, R3-33K-G5-L4, R3-36K-G5-L0, R3-36K-G5, R3-36K-G5-L1, R3-36K-G5-L2, R3-36K-G5-L3, R3-36K-G5-L4, R3-40K-G5-L0, R3-40K-G5, R3-40K-G5-L1, R3-40K-G5-L2, R3-40K-G5-L3, R3-40K-G5-L4

This certificate of conformity is based on the evaluation of samples of the product. It does not imply an assessment of the production and it does not permit the use of a mark of conformity or of a safety mark of the TÜV NORD CERT GmbH. The holder of this certificate may use this Certificate together with his EC-Declaration of Conformity.

Certification program:	P33-VA-01 Rev. 02 / 04.20
Certification fundamental(s):	IEC62109-1:2010; IEC62109-2:2011
Registered no.:	44 799 22 406749 - 022
Report no.:	492011956.001
File no.:	PVP12052/21B-01



TÜV NORD CERT GmbH
Certification Body
Balance of System (BOS) for Photovoltaics

Essen, 2022-03-02

TÜV NORD CERT GmbH

Am TÜV 1, D-45307 Essen

www.tuev-nord-cert.de

prodcert@tuev-nord.de

Please also pay attention to the information stated overleaf.

 The CE marking may be affixed on the product if all relevant and effective Directives are complied with. 

ANNEX

Annex 1, Page 1 of 25

to Certificate registration no. 44 799 22 406749 - 022

Description of product(s):

Model type	R3-40K-G5-L0		
General information			
Type of inverter	No-Isolated	Separated by	Transformer-less
Safety class.....	Class I	IP grade.....	IP66
Over-voltage category.....	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature.....	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight.....	32.5kg	Dimension (W x H x D).....	380mm x 483mm x 227mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0
PV input			
Vmax.....	1100V d.c.	Isc.....	40A d.c.*3
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking.....	3
Back-feed current.....	0A	Max input current.....	26A d.c.*3
AC output			
Rated output voltage.....	400/230V a.c. 3P+N+PE	Rated output frequency.....	50Hz/60Hz
Rated output power.....	40kW	Max. apparent power	44kVA
Max output current.....	63.8 A a.c.	Power factor	[-0.8, 0.8]



ANNEX

Annex 1, Page 2 of 25

to Certificate registration no. 44 799 22 406749 - 022

Model type	R3-40K-G5		
General information			
Type of inverter	No-Isolated	Separated by	Transformerless
Safety class.....	Class I	IP grade.....	IP66
Over-voltage category.....	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature.....	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight.....	32.5kg	Dimension (W x H x D).....	380mm x 483mm x 227mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0
PV input			
Vmax	1100V d.c.	Isc.....	40A d.c.*3
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking.....	3
Back-feed current.....	0A	Max input current.....	30A d.c.*3
AC output			
Rated output voltage.....	400/230V a.c. 3P+N+PE	Rated output frequency.....	50Hz/60Hz
Rated output power.....	40kW	Max. apparent power	44kVA



ANNEX

Annex 1, Page 3 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current..... :	63.8 A a.c.	Power factor	[-0.8, 0.8]
Model type	R3-40K-G5-L1		
General information			
Type of inverter	No-Isolated	Separated by	Transformer-less
Safety class.....	Class I	IP grade.....	IP66
Over-voltage category.....	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature.....	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight.....	32.5kg	Dimension (W x H x D).....	380mm x 483mm x 227mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0
PV input			
Vmax.....	1100V d.c.	Isc.....	60A/60A/30A
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking.....	3
Back-feed current.....	0A	Max input current.....	36A/36A/18A
AC output			
Rated output voltage.....	400/230V a.c. 3P+N+PE	Rated output frequency.....	50Hz/60Hz
Rated output power.....	40kW	Max. apparent power	44kVA



TÜV NORD CERT GmbH
 Certification Body
 Balance of System (BOS) for Photovoltaics

Essen, 2022-03-02

ANNEX

Annex 1, Page 4 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current.....:	63.8 A a.c.	Power factor	[-0.8, 0.8]
Model type	R3-40K-G5-L2		
General information			
Type of inverter	No-Isolated	Separated by	Transformer-less
Safety class.....:	Class I	IP grade.....:	IP66
Over-voltage category	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature.....:	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight.....:	32.5kg	Dimension (W x H x D)	380mm x 483mm x 227mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0
PV input			
Vmax.....:	1100V d.c.	Isc.....:	60A/60A/30A
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking.....:	3
Back-feed current.....:	0A	Max input current.....:	40A/40A/20A
AC output			
Rated output voltage.....:	400/230V a.c. 3P+N+PE	Rated output frequency.....:	50Hz/60Hz
Rated output power.....:	40kW	Max. apparent power	44kVA



ANNEX

Annex 1, Page 5 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current	63.8 A a.c.	Power factor	[-0.8, 0.8]
--------------------------	-------------	--------------------	-------------

Model type	R3-40K-G5-L3		
General information			
Type of inverter	No-Isolated	Separated by	Transformer-less
Safety class	Class I	IP grade	IP66
Over-voltage category	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight	32.5kg	Dimension (W x H x D)	380mm x 483mm x 227mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0
PV input			
Vmax	1100V d.c.	Isc	60A d.c.*2
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking	2
Back-feed current	0A	Max input current	40A d.c.*2
AC output			
Rated output voltage	400/230V a.c. 3P+N+PE	Rated output frequency	50Hz/60Hz
Rated output power	40kW	Max. apparent power	44kVA



TÜV NORD CERT GmbH
 Certification Body
 Balance of System (BOS) for Photovoltaics

Essen, 2022-03-02

ANNEX

Annex 1, Page 6 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current..... :	63.8 A a.c.	Power factor	[-0.8, 0.8]
---------------------------	-------------	--------------------	-------------

Model type	R3-40K-G5-L4		
------------------	--------------	--	--

General information			
Type of inverter	No-Isolated	Separated by	Transformer-less
Safety Class	Class I	IP grade	IP66
Over-voltage category..... :	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature..... :	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight..... :	32.5kg	Dimension (W x H x D)..... :	380mm x 483mm x 247mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0
PV input			
Vmax..... :	1100V d.c.	Isc..... :	60A/60A/40A
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking..... :	3
Back-feed current..... :	0A	Max input current..... :	39A/39A/26A
AC output			
Rated output voltage..... :	400/230V a.c. 3P+N+PE	Rated output frequency..... :	50Hz/60Hz
Rated output power..... :	40kW	Max. apparent power	44kVA



TÜV NORD CERT GmbH
 Certification Body
 Balance of System (BOS) for Photovoltaics

Essen, 2022-03-02

ANNEX

Annex 1, Page 7 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current	63.8 A a.c.	Power factor	[-0.8, 0.8]
Model type	R3-36K-G5-L0		
General information			
Type of inverter	No-Isolated	Separated by	Transformer-less
Safety Class	Class I	IP grade	IP66
Over-voltage category	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight	32.5kg	Dimension (W x H x D)	380mm x 483mm x 227mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0
PV input			
Vmax	1100V d.c.	Isc	40A d.c.*3
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking	3
Back-feed current	0A	Max input current	26A d.c.*3
AC output			
Rated output voltage	400/230V a.c. 3P+N+PE	Rated output frequency	50Hz/60Hz
Rated output power	36kW	Max. apparent power	39.6kVA



TÜV NORD CERT GmbH
 Certification Body
 Balance of System (BOS) for Photovoltaics

Essen, 2022-03-02

ANNEX

Annex 1, Page 8 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current	57.3 A a.c.	Power factor	[-0.8, 0.8]
Model type	R3-36K-G5		
General information			
Type of inverter	No-Isolated	Separated by	Transformer-less
Safety class	Class I	IP grade	IP66
Over-voltage category	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight	32.5kg	Dimension (W x H x D)	380mm x 483mm x 227mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0
PV input			
Vmax	1100V d.c.	Isc	40A d.c.*3
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking	3
Back-feed current	0A	Max input current	30A d.c.*3
AC output			
Rated output voltage	400/230V a.c. 3P+N+PE	Rated output frequency	50Hz/60Hz
Rated output power	36kW	Max. apparent power	39.6kVA



ANNEX

Annex 1, Page 9 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current.....:	57.3 A a.c.	Power factor	[-0.8, 0.8]
--------------------------	-------------	--------------------	-------------

Model type	R3-36K-G5-L1		
General information			
Type of inverter	No-Isolated	Separated by.....:	Transformer-less
Safety class.....:	Class I	IP grade.....:	IP66
Over-voltage category.....:	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature.....:	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight.....:	32.5kg	Dimension (W x H x D).....:	380mm x 483mm x 227mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0
PV input			
Vmax.....:	1100V d.c.	Isc.....:	60A/60A/30A
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking.....:	3
Back-feed current.....:	0A	Max input current.....:	36A/36A/18A
AC output			
Rated output voltage.....:	400/230V a.c. 3P+N+PE	Rated output frequency.....:	50Hz/60Hz
Rated output power.....:	36kW	Max. apparent power	39.6kVA



ANNEX

Annex 1, Page 10 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current.....:	57.3 A a.c.	Power factor	[-0.8, 0.8]
Model type	R3-36K-G5-L2		
General information			
Type of inverter	No-Isolated	Separated by	Transformer-less
Safety class.....:	Class I	IP grade.....:	IP66
Over-voltage category.....:	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature.....:	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight.....:	32.5kg	Dimension (W x H x D).....:	380mm x 483mm x 227mm
Firmware of control board.....:	0.0.0	Firmware of LCD	1.0.0
PV input			
Vmax.....:	1100V d.c.	Isc.....:	60A/60A/30A
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking.....:	3
Back-feed current.....:	0A	Max input current.....:	40A/40A/20A
AC output			
Rated output voltage.....:	400/230V a.c. 3P+N+PE	Rated output frequency.....:	50Hz/60Hz
Rated output power.....:	36kW	Max. apparent power	39.6kVA



TÜV NORD CERT GmbH
 Certification Body
 Balance of System (BOS) for Photovoltaics

Essen, 2022-03-02

ANNEX

Annex 1, Page 11 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current	57.3 A a.c.	Power factor	[-0.8, 0.8]
Model type	R3-36K-G5-L3		
General information			
Type of inverter	No-Isolated	Separated by	Transformer-less
Safety class	Class I	IP grade	IP66
Over-voltage category	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight	32.5kg	Dimension (W x H x D)	380mm x 483mm x 227mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0
PV input			
Vmax	1100V d.c.	Isc	60A d.c.*2
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking	2
Back-feed current	0A	Max input current	40A d.c.*2
AC output			
Rated output voltage	400/230V a.c. 3P+N+PE	Rated output frequency	50Hz/60Hz
Rated output power	36kW	Max. apparent power	39.6kVA



ANNEX

Annex 1, Page 12 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current	57.3 A a.c.	Power factor	[-0.8, 0.8]
Model type	R3-36K-G5-L4		
General information			
Type of inverter	No-Isolated	Separated by	Transformer-less
Safety class	Class I	IP grade	IP66
Over-voltage category	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight	32.5kg	Dimension (W x H x D)	380mm x 483mm x 247mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0
PV input			
Vmax	1100V d.c.	Isc	60A/60A/40A
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking	3
Back-feed current	0A	Max input current	39A/39A/26A
AC output			
Rated output voltage	400/230V a.c. 3P+N+PE	Rated output frequency	50Hz/60Hz
Rated output power	36kW	Max. apparent power	39.6kVA



ANNEX

Annex 1, Page 13 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current.....:	57.3 A a.c.	Power factor	[-0.8, 0.8]
Model type	R3-33K-G5-L0		
General information			
Type of inverter	No-Isolated	Separated by.....:	Transformer-less
Safety class.....:	Class I	IP grade.....:	IP66
Over-voltage category.....:	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature.....:	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight.....:	32.5kg	Dimension (W x H x D).....:	380mm x 483mm x 227mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0
PV input			
Vmax.....:	1100V d.c.	Isc.....:	40A d.c.*3
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking.....:	3
Back-feed current.....:	0A	Max input current.....:	26A d.c.*3
AC output			
Rated output voltage.....:	400/230V a.c. 3P+N+PE	Rated output frequency.....:	50Hz/60Hz
Rated output power.....:	33kW	Max. apparent power	36.3kVA



ANNEX

Annex 1, Page 14 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current	52.6 A a.c.	Power factor	[-0.8, 0.8]
Model type	R3-33K-G5		
General information			
Type of inverter	No-Isolated	Separated by	Transformer-less
Safety class	Class I	IP grade	IP66
Over-voltage category	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight	32.5kg	Dimension (W x H x D)	380mm x 483mm x 227mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0
PV input			
Vmax	1100V d.c.	Isc	40A d.c.*3
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking	3
Back-feed current	0A	Max input current	30A d.c.*3
AC output			
Rated output voltage	400/230V a.c. 3P+N+PE	Rated output frequency	50Hz/60Hz
Rated output power	33kW	Max. apparent power	36.3kVA



ANNEX

Annex 1, Page 15 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current	52.6 A a.c.	Power factor	[-0.8, 0.8]
--------------------------	-------------	--------------------	-------------

Model type	R3-33K-G5-L1		
------------------	--------------	--	--

General information

Type of inverter	No-Isolated	Separated by	Transformer-less
Safety class.....	Class I	IP grade.....	IP66
Over-voltage category.....	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature.....	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight.....	32.5kg	Dimension (W x H x D).....	380mm x 483mm x 227mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0

PV input

Vmax.....	1100V d.c.	Isc.....	60A/60A/30A
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking.....	3
Back-feed current.....	0A	Max input current.....	36A/36A/18A

AC output

Rated output voltage.....	400/230V a.c. 3P+N+PE	Rated output frequency.....	50Hz/60Hz
Rated output power.....	33kW	Max. apparent power	36.3kVA



ANNEX

Annex 1, Page 16 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current.....:	52.6 A a.c.	Power factor	[-0.8, 0.8]
Model type	R3-33K-G5-L2		
General information			
Type of inverter	No-Isolated	Separated by	Transformer-less
Safety class.....:	Class I	IP grade.....:	IP66
Over-voltage category.....:	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature.....:	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight.....:	32.5kg	Dimension (W x H x D).....:	380mm x 483mm x 227mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0
PV input			
Vmax.....:	1100V d.c.	Isc.....:	60A/60A/30A
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking.....:	3
Back-feed current.....:	0A	Max input current.....:	40A/40A/20A
AC output			
Rated output voltage.....:	400/230V a.c. 3P+N+PE	Rated output frequency.....:	50Hz/60Hz
Rated output power.....:	33kW	Max. apparent power	36.3kVA



TÜV NORD CERT GmbH
 Certification Body
 Balance of System (BOS) for Photovoltaics

Essen, 2022-03-02

ANNEX

Annex 1, Page 17 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current	52.6 A a.c.	Power factor	[-0.8, 0.8]
Model type	R3-33K-G5-L3		
General information			
Type of inverter	No-Isolated	Separated by	Transformer-less
Safety class	Class I	IP grade	IP66
Over-voltage category	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight	32.5kg	Dimension (W x H x D)	380mm x 483mm x 227mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0
PV input			
Vmax	1100V d.c.	Isc	60A d.c.*2
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking	2
Back-feed current	0A	Max input current	40A d.c.*2
AC output			
Rated output voltage	400/230V a.c. 3P+N+PE	Rated output frequency	50Hz/60Hz
Rated output power	33kW	Max. apparent power	36.3kVA



ANNEX

Annex 1, Page 18 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current	52.6 A a.c.	Power factor	[-0.8, 0.8]
Model type	R3-33K-G5-L4		
General information			
Type of inverter	No-Isolated	Separated by	Transformer-less
Safety class	Class I	IP grade	IP66
Over-voltage category	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight	32.5kg	Dimension (W x H x D)	380mm x 483mm x 247mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0
PV input			
Vmax	1100V d.c.	Isc	60A/60A/40A
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking	3
Back-feed current	0A	Max input current	39A/39A/26A
AC output			
Rated output voltage	400/230V a.c. 3P+N+PE	Rated output frequency	50Hz/60Hz
Rated output power	33kW	Max. apparent power	36.3kVA



ANNEX

Annex 1, Page 19 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current	52.6 A a.c.	Power factor	[-0.8, 0.8]
Model type	R3-30K-G5-L0		
General information			
Type of inverter	No-Isolated	Separated by	Transformer-less
Safety class.....	Class I	IP grade.....	IP66
Over-voltage category.....	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature.....	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight.....	32.5kg	Dimension (W x H x D).....	380mm x 483mm x 227mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0
PV input			
Vmax.....	1100V d.c.	Isc.....	40A d.c.*3
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking.....	3
Back-feed current.....	0A	Max input current.....	26A d.c.*3
AC output			
Rated output voltage.....	400/230V a.c. 3P+N+PE	Rated output frequency.....	50Hz/60Hz
Rated output power.....	30kW	Max. apparent power	33kVA



ANNEX

Annex 1, Page 20 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current	47.8A a.c.	Power factor	[-0.8, 0.8]
Model type	R3-30K-G5		
General information			
Type of inverter	No-Isolated	Separated by	Transformer-less
Safety class	Class I	IP grade	IP66
Over-voltage category	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight	32.5kg	Dimension (W x H x D)	380mm x 483mm x 227mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0
PV input			
Vmax	1100V d.c.	Isc	40A d.c.*3
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking	3
Back-feed current	0A	Max input current	30A d.c.*3
AC output			
Rated output voltage	400/230V a.c. 3P+N+PE	Rated output frequency	50Hz/60Hz
Rated output power	30kW	Max. apparent power	33kVA



ANNEX

Annex 1, Page 21 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current	47.8A a.c.	Power factor	[-0.8, 0.8]
Model type	R3-30K-G5-L1		
General information			
Type of inverter	No-Isolated	Separated by	Transformer-less
Safety class.....	Class I	IP grade.....	IP66
Over-voltage category.....	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature.....	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight.....	32.5kg	Dimension (W x H x D).....	380mm x 483mm x 227mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0
PV input			
Vmax.....	1100V d.c.	Isc.....	60A/60A/30A
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking.....	3
Back-feed current.....	0A	Max input current.....	36A/36A/18A
AC output			
Rated output voltage.....	400/230V a.c. 3P+N+PE	Rated output frequency.....	50Hz/60Hz
Rated output power.....	30kW	Max. apparent power	33kVA



ANNEX

Annex 1, Page 22 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current.....:	47.8A a.c.	Power factor	[-0.8, 0.8]
--------------------------	------------	--------------------	-------------

Model type	R3-30K-G5-L2		
------------------	--------------	--	--

General information

Type of inverter	No-Isolated	Separated by.....:	Transformer-less
Safety class.....:	Class I	IP grade.....:	IP66
Over-voltage category.....:	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature.....:	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight.....:	32.5kg	Dimension (W x H x D).....:	380mm x 483mm x 227mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0

PV input

Vmax.....:	1100V d.c.	Isc.....:	60A/60A/30A
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking.....:	3
Back-feed current.....:	0A	Max input current.....:	40A/40A/20A

AC output

Rated output voltage.....:	400/230V a.c. 3P+N+PE	Rated output frequency.....:	50Hz/60Hz
Rated output power.....:	30kW	Max. apparent power	33kVA



ANNEX

Annex 1, Page 23 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current	47.8A a.c.	Power factor	[-0.8, 0.8]
Model type	R3-30K-G5-L3		
General information			
Type of inverter	No-Isolated	Separated by	Transformer-less
Safety class	Class I	IP grade	IP66
Over-voltage category	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight	32.5kg	Dimension (W x H x D)	380mm x 483mm x 227mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0
PV input			
Vmax	1100V d.c.	Isc	60A d.c.*2
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking	2
Back-feed current	0A	Max input current	40A d.c.*2
AC output			
Rated output voltage	400/230V a.c. 3P+N+PE	Rated output frequency	50Hz/60Hz
Rated output power	30kW	Max. apparent power	33kVA



ANNEX

Annex 1, Page 24 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current	47.8A a.c.	Power factor	[-0.8, 0.8]
Model type	R3-30K-G5-L4		
General information			
Type of inverter	No-Isolated	Separated by	Transformer-less
Safety class	Class I	IP grade	IP66
Over-voltage category	PV Input: II AC Output: III	Pollution degree	External: 3 Internal: 2
Operating temperature	-25°C to 60°C (>45°C derating)	Altitude	4000m (>3000m derating)
Weight	32.5kg	Dimension (W x H x D)	380mm x 483mm x 247mm
Firmware of control board	0.0.0	Firmware of LCD	1.0.0
PV input			
Vmax	1100V d.c.	Isc	60A/60A/40A
MPP voltage range	200V d.c. - 1000V d.c.	Number of MPPT tracking	3
Back-feed current	0A	Max input current	39A/39A/26A
AC output			
Rated output voltage	400/230V a.c. 3P+N+PE	Rated output frequency	50Hz/60Hz
Rated output power	30kW	Max. apparent power	33kVA



ANNEX

Annex 1, Page 25 of 25

to Certificate registration no. 44 799 22 406749 - 022

Max output current	47.8A a.c.	Power factor	[-0.8, 0.8]
--------------------------	------------	--------------------	-------------

Remark:

For detailed product information, please refer to CDF (Constructional Data Form) in Annex 2 of test report.

