

Residential On-grid Inverter

R1 Moto Series

8kW / 10kW / 10.5kW



Features

Single Phase, 2 MPPTs

-  Compatible with 500W+ PV modules
-  Optional AFCI protection function
-  150% PV input oversizing
-  Remote firmware upgrade
-  Type II SPD for both DC and AC
-  Built-in zero export function



Model	R1-8K	R1-10K	R1-10K5
PV Input			
Max. Recommended PV Power [Wp]	12000	15000	16000
Max. #PV#Power for single MPPT [kW]	6000	7500	7500
Max. #PV/ Input Voltage [V]		600	
MPPT Voltage Range [V]		80 ~ 550	
Rated PV Input Voltage [V]		360	
Start-up Voltage [V]		100	
No. of MPP Trackers	2	2	2
No. of Input Strings per Tracker	2 / 2	2 / 2	2 / 2
Max. PV Input Current [A]	32 / 32	32 / 32	32 / 32
Max. Short-circuit Current [A]	40 / 40	40 / 40	40 / 40
AC Output			
Rated AC Output Power [W]	8000	10000	10500
Max. AC Output Apparent Power [VA]	8800	10000	10500
Max. AC Output Current [A]	40	45.5	45.5
Rated AC Voltage [V]		L / N / PE, 220 / 230	
Grid Frequency [Hz]		50 / 60	
Adjustable Power Factor [cosφ]		0.8 leading ~ 0.8 lagging	
Output THDi (@Rated Output)		< 3%	
Efficiency			
Max. Efficiency	98.1%	98.1%	98.1%
Euro Efficiency	97.5%	97.5%	97.5%
Protection			
DC Insulation Monitoring		Integrated	
Input Reverse Polarity Protection		Integrated	
Anti-island Protection		Integrated	
Residual Current Monitoring		Integrated	
AC Overcurrent Protection		Integrated	
AC Short-circuit Protection		Integrated	
DC Surge Protection		Integrated(Type II)	
AC Surge Protection		Integrated(Type II)	
AFCI Protection		Optional	
DC Switch		Optional	
General Data			
Dimensions (W * H * D) [mm]		428 * 385 * 185	
Weight [kg]		17	
Display		LED + OLED	
Communication		RS485, USB Upgrade, Optional: Wifi, 4G, Ethernet	
Ambient Temperature Range [°C]		-25 ~ +60	
Relative Humidity		0 ~ 100%	
Operating Altitude [m]		≤ 2000	
Night Self-consumption [W]		< 1	
Topology		Transformerless	
Cooling		Natural	
Ingress Protection		IP65	
Noise [dB]		< 35	
Certifications & Standards			
Grid Regulation		ORDINANCE No.140	
Safety Regulation		IEC 62109-1, IEC 62109-2, EN 62919-1, EN 62619-2	
EMC		EN IEC 61000-6-1, EN IEC 61000-6-3	